

# 4activeHT

### 4activeHT - heated cover dummy


- ✓ for testing passive IR-systems like night vision
- ✓ applicable as a static or moving object
- compatible with 4activeSB, 4activeXB, 4activeFB-small, 4activeFB-eco

## Optimal heat transfer due to battery powered heated cover

- power supply (2x12V) via trailing cable
- ✓ heating mats ensure an optimal heat transfer to the outer surface
- control of 5 different heating zones: head, torso, legs, hands, arms

### **Available options**

- ✓ 4activePA-HT heated articulated pedestrian target
- ✓ 4activeAN-HT heated animal target



# 4activeHT

## **Dimensions 4activePS-HT**

| body height adult | 1800 mm  |
|-------------------|----------|
| weight adult      | < 8 kg*  |
| body height child | 1154 mm  |
| weight child      | < 4 kg * |

#### **Dimensions 4activePA-HT**

| body height adult | 1800 mm  |
|-------------------|----------|
| weight adult      | < 10 kg* |
| body height child | 1154 mm  |
| weight child      | < 5 kg*  |

## **Dimensions 4activeAN-HT**

| body height roe deer | 170 mm  |
|----------------------|---------|
| weight               | < 6 kg* |

#### **Performance**

| collision speed crossing scenario     | up to 30 km/h (18 mph) |
|---------------------------------------|------------------------|
| collision speed longitudinal scenario | Δv 20 km/h (12 mph)    |

★ weight excl. accessories (batteries, cable)

#### **Key features**

- compatible with 4activeSB, 4activeXB, 4activeFB-small, 4activeFB-eco
- ✓ for testing passive IR-systems like night vision
- ✓ heating control unit to control five different zones
- power supply (2x12V) via trailing cable



W