



I N P H Y S I C S W E T R U S T

## 4activePS

### 4activePS - static pedestrian target


- ✓ available as 50% adult male, 7-year, 2-year, 1-year old child
- ✓ replicates human properties in size, shape and articulation
- ✓ complies with ISO 19237, ISO 19206-2, Euro NCAP, JNCAP, ...

### Allows testing under rough conditions

- ✓ extremely light and soft structure to prevent damage on VUT
- ✓ robust and modular system – easy and fast change of spare parts
- ✓ realistic response for Radar-, Lidar, Camera and IR-Systems

### Available options

- ✓ 50% adult male
- ✓ 7-year, 2-year, 1-year old child
- ✓ heated pedestrian target – 4activeHT



# 4activePS

## Performance

mono/stereo camera system, Lidar sensors	✓
360° - Radar characteristic	✓
micro-Doppler spread	✓
near infrared / far infraredstar*	✓
ultra-sonic	✓
crash speed	up to 60 km/h
operation speed	up to 10 km/h

★ optional

## Dimensions adult

body height	1800 mm
shoulder width	500 mm
torso angle	85 °
weight	< 4 kg** / 7,5 kg ***

★★4activePS ★★★4activePA

## Dimensions child

body height	1154 mm
shoulder width	298 mm
torso angle	78 °
weight	< 2 kg** / 4 kg ***

★★4activePS ★★★4activePA

## Key features

- ✓ compatible with 4activeSB, 4activeFB-small, 4activeFB-eco
- ✓ absolute waterproof - testing under rainy conditions
- ✓ extremely light
- ✓ soft structure to prevent damage on VUT

