

4activeBS-adult



Official Euro NCAP bicyclist target (EBT)

- standard average european utility bike average male
- ✓ realistic properties in size, shape and rotating wheels
- complies with ISO 19206-4, Euro NCAP, UN-ECE, ...

Allows testing under rough conditions

- extremely light and soft structure to prevent damage on VUT
- ✓ robust, modular and weatherproof system easy and fast change of spare parts
- ☑ realistic response for Radar-, Lidar-, Camera-, Ultrasonic- and IR-Systems

Available options

- ✓ heated bicyclist target 4activeHT
- synchronized articulation (pedalling, arm movement, head rotation, ...)
- ✓ additional active light-kit





4activeBS-adult

Performance

mono/stereo camera system, Lidar sensors	✓	
360° - Radar characteristic	✓	
micro-Doppler spread	✓	
near infrared / far infrared★	✓	
ultrasonic	✓	
crash speed lateral / longitudinal	up to 60 km/h / up to 45 km/h	
operation speed	up to 35 km/h	
		★ optional

Dimensions bike

handlebar height	1200 mm
diameter wheels	700 mm
wheel base	1230 mm
weight	6 kg

Dimensions bicyclist

body height	1800 mm
shoulder width	500 mm
torso angle	10°
weight	< 4 kg

Key features

- compatible with 4activeSB, 4activeXB, 4activeFB-small, 4activeFB-eco
- ✓ rotating wheels permanent contact to ground
- ✓ disassembable bike easy transportation and storage



N PHYSICS

W E

R

u s